

GAS STATION INFORMATION

- **Fuel selection:**

Select premium unleaded gasoline with an Octane Rating of 91 (Research Octane Number 96) or higher for optimum engine performance. However, if such premium type cannot be obtained, you may temporarily use unleaded gasoline with an Octane Rating as low as 87 (Research Octane Number 91).

- **Fuel tank capacity:**

66 L (17.5 gal., 14.5 Imp.gal.)

- **Engine oil:**

API SJ, "Energy-Conserving" multigrade engine oil or ILSAC multigrade engine oil.

Recommend oil viscosity – SAE 5W-30 if normal temperatures are below 38°C (100°F)

Oil capacity: L (qt., Imp.qt.)

Drain and refill	
with filter	5.4 (5.7, 4.8)
without filter	5.1 (5.4, 4.5)

See page 242 for detailed information.

- **Engine coolant:**

Capacity: 7.5 L (7.9 qt., 6.6 Imp.qt.)

Coolant type – "Toyota Long Life Coolant" or equivalent

With ethylene-glycol type coolant for a proper corrosion protection of aluminum components

For checking the engine coolant, see page 245.

Do not use alcohol type antifreeze or plain water alone.

- **Automatic transmission:**

Fluid type – **Automatic transmission fluid Type T-IV**

See page 248 for detailed information.

- **Tire information:**

See page 254 through 260 for detailed information.

- **Tire pressure:**

Tire size: 215/45ZR17 or P205/55R16 89V

Tire pressure: cold tires
kPa (kgf/cm² or bar, psi)

<u>Tire size</u>	<u>Front</u>	<u>Rear</u>
215/45ZR17	230 (2.3, 33)	230 (2.3, 33)
P205/55R16 89V	230 (2.3, 33)	230 (2.3, 33)

For sustained high speeds above 160 km/h (100 mph), in countries where such speeds are permitted by law, add the tire pressure given below to the front tires and rear tires, but never exceed the maximum cold tire pressure molded on the tire sidewall.

215/45ZR17	70kPa (0.8 kgf/cm ² , 0.7 bar, 10 psi)
P205/55R16 89V	70kPa (0.8 kgf/cm ² , 0.7 bar, 10 psi)